



HSS RECTANGLE

DIMENSIONS		WEIGHT	LENGTHS					GRADES	
OD (inches)	Wall (inches)	Per ft (lbs)	20'	24'	40'	48'	30/60'	CSA G40	ASTM A500C
2.000 x 1.000	0.100	1.82		✓					✓
	0.125	2.21		✓					✓
	0.188	3.05		✓					✓
2.500 x 1.500	0.125	3.06		✓					✓
	0.188	4.33		✓					✓
	0.250	5.41		✓					✓
3.000 x 1.000	0.125	3.06		✓					✓
	0.188	4.33		✓					✓
3.000 x 1.500	0.125	3.48	✓	✓	✓				✓
	0.188	4.96		✓				✓	✓
3.000 x 2.000	0.125	3.91	✓	✓	✓	✓		✓	✓
	0.188	5.61	✓	✓	✓			✓	✓
	0.250	7.11	✓	✓	✓	✓		✓	✓
	0.313	8.15	✓		✓				✓
3.500 x 2.500	0.250	8.81		✓		✓			✓
4.000 x 2.000	0.125	4.76		✓		✓			✓
	0.188	6.89	✓	✓	✓	✓		✓	✓
	0.250	8.81	✓	✓	✓	✓		✓	✓
	0.313	10.59		✓		✓		✓	✓
	0.375	12.17		✓		✓			✓
4.000 x 3.000	0.125	5.61	✓	✓	✓	✓		✓	✓
	0.188	8.17	✓	✓	✓	✓		✓	✓
	0.250	10.51	✓	✓	✓	✓		✓	✓
	0.313	12.70	✓	✓	✓	✓		✓	✓
	0.375	14.71	✓	✓	✓	✓		✓	✓
5.000 x 2.000	0.125	5.61		✓		✓		✓	✓
	0.188	8.17	✓	✓	✓	✓		✓	✓
	0.250	10.51	✓	✓	✓	✓		✓	✓
	0.313	12.70	✓		✓			✓	✓
	0.375	14.71	✓		✓				✓
5.000 x 2.500	0.188	8.80	✓	✓	✓				✓
	0.250	11.35		✓		✓			✓
5.000 x 3.000	0.188	9.45	✓	✓	✓	✓		✓	✓
	0.250	12.21	✓	✓	✓	✓		✓	✓
	0.313	14.84	✓	✓	✓	✓		✓	✓
	0.375	17.27	✓	✓	✓	✓		✓	✓
	0.500	21.64		✓		✓			✓

HSS RECTANGLE pg.2

DIMENSIONS		WEIGHT	LENGTHS					GRADES	
OD (inches)	Wall (inches)	Per ft (lbs)	20'	24'	40'	48'	30/60'	CSA G40	ASTM A500C
5.000 x 4.000	0.250	13.91	✓	✓	✓	✓			✓
	0.375	19.82		✓		✓			✓
6.000 x 2.000	0.125	6.46	✓	✓	✓	✓		✓	✓
	0.188	9.45	✓	✓	✓	✓		✓	✓
	0.250	12.21	✓	✓	✓	✓		✓	✓
	0.375	17.27	✓	✓	✓	✓			✓
6.000 x 3.000	0.188	10.70	✓	✓	✓	✓		✓	✓
	0.250	13.91	✓	✓	✓	✓		✓	✓
	0.313	16.96	✓	✓	✓	✓		✓	✓
	0.375	19.82	✓	✓	✓	✓		✓	✓
	0.500	25.01	✓	✓	✓	✓			✓
6.000 x 4.000	0.188	12.00	✓	✓	✓	✓	✓	✓	✓
	0.250	15.62	✓	✓	✓	✓	✓	✓	✓
	0.313	19.08	✓	✓	✓	✓	✓	✓	✓
	0.375	22.37	✓	✓	✓	✓	✓	✓	✓
	0.500	28.43	✓	✓	✓	✓	✓	✓	✓
7.000 x 3.000	0.250	15.62	✓		✓				✓
7.000 x 4.000	0.250	17.32	✓	✓	✓	✓		✓	✓
7.000 x 5.000	0.188	14.56	✓	✓	✓	✓		✓	✓
	0.250	19.02	✓	✓	✓	✓		✓	✓
	0.313	23.35	✓	✓	✓	✓		✓	✓
	0.375	27.48	✓		✓	✓		✓	✓
	0.500	35.24	✓	✓	✓	✓		✓	✓
8.000 x 2.000	0.125	8.15	✓		✓				✓
	0.188	12.00	✓	✓	✓	✓		✓	✓
	0.250	15.62	✓	✓	✓	✓		✓	✓
	0.375	22.37	✓	✓	✓	✓			✓
8.000 x 3.000	0.188	13.28		✓		✓		✓	✓
	0.250	17.32	✓	✓	✓	✓		✓	✓
	0.375	24.90	✓	✓	✓	✓			✓
8.000 x 4.000	0.188	14.56	✓	✓	✓	✓		✓	✓
	0.250	19.02	✓	✓	✓	✓		✓	✓
	0.313	23.35	✓	✓	✓	✓		✓	✓
	0.375	27.48	✓	✓	✓	✓		✓	✓
	0.500	35.24	✓	✓	✓	✓		✓	✓
8.000 x 6.000	0.188	17.13	✓	✓	✓	✓		✓	✓
	0.250	22.42	✓	✓	✓	✓		✓	✓
	0.313	27.63	✓	✓	✓	✓		✓	✓
	0.375	32.58	✓	✓	✓	✓		✓	✓
	0.500	42.05	✓	✓	✓	✓		✓	✓
	0.625	50.81		✓		✓			✓
9.000 x 7.000	0.375	37.69					✓		✓

HSS RECTANGLE pg.3

DIMENSIONS		WEIGHT	LENGTHS					GRADES	
OD (inches)	Wall (inches)	Per ft (lbs)	20'	24'	40'	48'	30/60'	CSA G40	ASTM A500C
10.000 x 2.000	0.188	14.60	✓	✓	✓	✓			✓
	0.250	19.02	✓	✓	✓	✓			✓
	0.375	27.48	✓		✓				✓
10.000 x 4.000	0.188	17.13	✓		✓			✓	✓
	0.250	22.42	✓	✓	✓	✓		✓	✓
	0.313	27.63	✓	✓	✓	✓		✓	✓
	0.375	32.58	✓	✓	✓	✓		✓	✓
	0.500	42.05	✓	✓	✓	✓		✓	✓
10.000 x 6.000	0.188	19.66	✓	✓	✓	✓		✓	✓
	0.250	25.82	✓	✓	✓	✓		✓	✓
	0.313	31.86	✓	✓	✓	✓		✓	✓
	0.375	37.69	✓	✓	✓	✓		✓	✓
	0.500	48.85	✓	✓	✓	✓		✓	✓
10.000 x 8.000	0.250	29.23	✓	✓	✓	✓		✓	✓
	0.375	42.78	✓	✓	✓	✓		✓	✓
	0.500	55.66	✓	✓	✓	✓		✓	✓
12.000 x 2.000	0.250	22.42	✓	✓	✓	✓		✓	✓
12.000 x 3.000	0.250	24.12	✓	✓	✓	✓			✓
12.000 x 4.000	0.188	19.66	✓	✓	✓	✓		✓	✓
	0.250	25.82	✓	✓	✓	✓		✓	✓
	0.375	37.69	✓	✓	✓	✓		✓	✓
	0.500	48.85	✓	✓	✓	✓		✓	✓
12.000 x 6.000	0.250	29.23	✓	✓	✓	✓		✓	✓
	0.313	36.14	✓	✓	✓	✓		✓	✓
	0.375	42.79	✓	✓	✓	✓		✓	✓
	0.500	55.66	✓	✓	✓	✓		✓	✓
12.000 x 8.000	0.250	32.63	✓	✓	✓	✓		✓	✓
	0.313	40.37	✓	✓	✓	✓		✓	✓
	0.375	47.90	✓	✓	✓	✓		✓	✓
	0.500	62.46	✓	✓	✓	✓		✓	✓