



HSS ROUNDS

DIMENSIONS		Weight/ft (lbs)	LENGTHS					GRADES	
OD (inches)	Wall (inches)		20'	24'	40'	48'	30/60'	CSA G40	ASTM A500C
1.050	0.100	1.02		✓					✓
1.315	0.100	1.30		✓					✓
	0.125	1.59		✓					✓
1.660	0.100	1.67		✓					✓
	0.125	2.05		✓					✓
	0.140	2.27		✓					✓
1.900	0.100	1.92		✓					✓
	0.125	2.37		✓					✓
	0.145	2.72		✓					✓
	0.188	3.44		✓				✓	✓
2.375	0.125	3.01		✓					✓
	0.154	3.65		✓					✓
	0.188	4.40		✓					✓
	0.250	5.68		✓					✓
2.875	0.188	5.40		✓					✓
	0.203	5.80	✓	✓		✓			✓
	0.250	7.00		✓		✓			✓
3.000	0.125	3.84		✓		✓			✓
	0.188	5.66		✓					✓
	0.250	7.35		✓		✓			✓
3.500	0.125	4.51		✓		✓			✓
	0.188	6.66		✓		✓			✓
	0.216	7.58	✓		✓				✓
	0.250	8.69	✓	✓	✓	✓			✓
	0.300	10.25	✓		✓				✓
4.000	0.125	5.17	✓	✓	✓	✓			✓
	0.188	7.67	✓	✓	✓	✓			✓
	0.226	9.11	✓	✓	✓	✓			✓
	0.250	10.02		✓		✓			✓
	0.313	12.33	✓	✓	✓	✓			✓
4.500	0.188	8.66		✓		✓			✓
	0.237	10.79	✓		✓				✓
	0.250	11.35	✓	✓	✓	✓			✓
	0.337	14.98	✓	✓	✓	✓			✓
	0.375	16.54	✓	✓	✓	✓			✓
5.000	0.125	6.52	✓	✓	✓	✓			✓
	0.188	9.67	✓	✓	✓	✓			✓
	0.250	12.68	✓	✓	✓	✓			✓
	0.375	18.52		✓		✓			✓

HSS ROUNDS pg.2

DIMENSIONS		Weight/ft (lbs)	LENGTHS					GRADES	
OD (inches)	Wall (inches)		20'	24'	40'	48'	30/60'	CSA G40	ASTM A500C
5.563	0.188	10.80	✓	✓	✓	✓			✓
	0.258	14.62		✓		✓			✓
	0.375	20.78		✓		✓			✓
6.000	0.188	11.67	✓	✓	✓	✓			✓
	0.250	15.35				✓			✓
	0.375	22.53	✓	✓	✓				✓
	0.500	29.37	✓	✓	✓	✓			✓
6.625	0.188	12.92	✓	✓	✓	✓			✓
	0.25	17.02	✓	✓	✓	✓			✓
	0.28	18.97	✓	✓	✓	✓			✓
	0.375	25.03	✓	✓	✓	✓			✓
	0.432	28.57	✓	✓	✓	✓			✓
	0.500	32.7	✓		✓				✓
7.000	0.500	34.17	✓	✓	✓	✓			✓
8.625	0.322	28.55	✓	✓	✓	✓			✓
	0.375	33.04	✓	✓	✓	✓			✓
	0.500	43.39	✓	✓	✓	✓			✓